

Palo PA-220 - security appliance

Insight # PAN-PA-220 Mfr. # PAN-PA-220 UNSPSC: 43170000

☆☆☆☆☆ [No reviews yet.](#)

List Price

USD \$1,395.99

Estimate the total price of this item

Stock

Call for Availability

Processor / Memory / Storage: SSD 32 GB x 1

Networking: External

Expansion / Connectivity: 8 x 1000Base-T - RJ-45

Miscellaneous: FCC Class A certified, CB, cCSAus, VCCI Class B



Palo PA-220 - Security appliance - GigE

Specifications

General

Device Type	Security appliance
Width	8.1 in
Depth	6.3 in
Height	1.6 in
Weight	3 lbs

Processor / Memory / Storage

Hard Drive	SSD 32 GB x 1
------------	---------------

Networking

Form Factor	External
Connectivity Technology	Wired
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Network / Transport Protocol	PPPoE

Welcome to Insight! What led you to stop by today?

Networking	
Routing Protocol	RIP, BGP, IGMPv2, IGMP, OSPFv2, PIM-SM, IGMPv3, OSPFv3, PIM-SSM, static IPv4 routing, Bidirectional Forwarding Detection (BFD)
Remote Management Protocol	SSH
Performance	Firewall throughput: 500 Mbps Threat prevention throughput: 150 Mbps VPN throughput (IPSec): 100 Mbps
Capacity	New sessions per second: 4200 Maximum number of sessions: 64000 VLAN tags per device: 4094 VLAN tags per interface: 4094 IPSec VPN tunnels: 250 Virtual routers: 3 Security zones: 15 Maximum number of policies: 250
Features	Firewall protection, NAT support, LDAP support, VLAN support, IPv6 support, High Availability, IPSec Virtual Private Network (VPN), IPv4 support
Encryption Algorithm	Triple DES, MD5, IKE, SSL, SHA-1, 128-bit AES, 192-bit AES, 256-bit AES, IKEv2, 384-bit SHA-2, 256-bit SHA, 512-bit SHA-2
Compliant Standards	IEEE 802.1Q

Expansion / Connectivity	
Interfaces	8 x 1000Base-T - RJ-45 1 x 1000Base-T (management) - RJ-45 1 x console - RJ-45 1 x USB 1 x console

Miscellaneous	
Compliant Standards	FCC Class A certified, CB, cCSAus, VCCI Class B

Power	
Power Device	Internal power supply
Installed Qty	2
Max Supported Qty	2
Power Redundancy	Yes
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	75 Watt
Power Provided	40 Watt

Environmental Parameters	
Min Operating Temperature	32 °F
Max Operating Temperature	104 °F

No warranties found for this item.

Welcome to Insight! What led you to stop by today?